



OLIVE SELECTION CONVEYOR BELTS



STANDART TYPE SELECTION CONVEYOR BELT WITH DEPOT

OUR SELECTION BELTS PROVIDE HEALTHY SELECTION PROCESS WITH DIFFERENT PRODUCTS REGULARY. BECAUSE OF THE APPARATUS LOCATED ON THE EXIT CHUTE. PRODUCTS CAN BE FILLED DIRECTLY INTO THE PACKAGES. THUS, PRODUCTS CAN BE PACKAGED WITHOUT MISUSING AND WITH LOWER PRICE. OUR SELECTION BELTS WHICH ARE SEEN IN THE PICTURES, IN THREE STANDARD TYPE; WITH THREE WAYS, WITH LIGHTS AND WITH DEPOT FOR ACUPLE PRODUCTS.ACCORDING TO THE CUSTOMERS' NEED. THE BELTS FOR FEEDING PRODUCTS CAN BE INSTALLED ON THE MACHINE.BY THE HELP OF SPEED CONTROL DEVICE, SPEED OF WALKING BELT CAN BE HOLDED AT ANY LEVEL.BELT USED ON THE MACHINE IS APPROPRIATE FOR REGULATIONS OF GOOD. BELTS ARE MANUFACTURED IN WHITE, DARK BLUE AND GREEN COLOUR ACCORDING TO THE PRODUCT TYPE. ALL OF THE COMPONENTS OF THE MACHINE ARE MANUFACTURED FROM CrNi (CHROMIUM NICKEL) OF QUALITY 304

TECHNICAL SPECIFICATIONS

Model	OPM 404	OPM 405	OPM 406	OPM 408	OPM 410
Belt Usage Length	4000 mm	5000 mm	6000 mm	8000 mm	10000 mm
Belt Usage Width	750 mm	750 mm	750 mm	750 mm	750 mm
Depot Capacity	100 Kg.	100 Kg.	100 Kg.	100 Kg.	100 Kg.
Motor Power	0,55 Kw	0,55 Kw	0,75 Kw	1,1 Kw	1,1 Kw
Belt Speed (Max)	6 Mt/Min.	6 Mt/Min.	6 Mt/Min.	7 Mt/Min.	7 Mt/Min.
Quality of Material	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi

MEASUREMENTS (mm)

	Chassis Length	Total Length	Total Width	Total Height	Chassis Height	Chassis Width
OPM 404	4000	5000	1000	1350	850	850
OPM 405	5000	6000	1000	1350	850	850
OPM 406	6000	7000	1000	1350	850	850
OPM 408	8000	9000	1000	1350	850	850
OPM 410	10000	11000	1000	1350	850	850



SELECTION BELT WITH LOADING ELEVATOR

OUR SELECTION BELTS PROVIDE HEALTHY SELECTION PROCESS WITH DIFFERENT PRODUCTS REGULARY. BECAUSE OF THE APPARATUS LOCATED ON THE EXIT CHUTE, PRODUCTS CAN BE FILLED INTO THE PACKAGES DIRECTLY. THUS, PRODUCTS CAN BE PACKAGED WITHOUT MISUSING AND WITH LOWER PRICE. OUR SELECTION BELTS WHICH ARE SEEN IN THE PICTURES, IN THREE STANDARD TYPE, WITH THREE WAYS, WITH LIGHTS AND WITH DEPOT FOR ACUPLE PRODUCTS. ACCORDING TO THE CUSTOMERS' NEED. THE BELTS FOR FEEDING PRODUCTS CAN BE INSTALLED ON THE MACHINE. BY THE HELP OF THE SPEED CONTROL DEVICE, SPEED OF WALKING BELT CAN BE HOLDED AT ANY LEVEL. BELT USED ON THE MACHINE IS APPROPRIATE FOR REGULATIONS OF GOOD. THE BELTS ARE MANUFACTURED IN WHITE, DARK BLUE AND GREEN COLOUR ACCORDING TO THE PRODUCT TYPE. ALL OF THE COMPONENTS OF THE MACHINE ARE MANUFACTURED FROM CrNi (CHROMIUM NICKEL) OF QUALITY 304

TECHNICAL SPECIFICATIONS

Model	OPM 414	OPM 415	OPM 416	OPM 418	OPM 420
Belt Usage Length	4000 mm	5000 mm	6000 mm	8000 mm	10000 mm
Belt Usage Width	750 mm	750 mm	750 mm	750 mm	750 mm
Depot Capacity	100 Kg.	100 Kg.	100 Kg.	100 Kg.	100 Kg.
Motor Power	0,55 Kw	0,55 Kw	0,75 Kw	1,1 Kw	1,1 Kw
Belt Speed (Max)	6 Mt/Min.	6 Mt/Min.	6 Mt/Min.	7 Mt/Min.	7 Mt/Min.
Quality of Material	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi

MEASUREMENTS (mm)

	Chassis Length	Total Length	Total Width	Total Height	Chassis Height	Chassis Width
OPM 414	4000	6000	1000	1300	850	850
OPM 415	5000	7000	1000	1300	850	850
OPM 416	6000	8000	1000	1300	850	850
OPM 418	8000	10000	1000	1300	850	850
OPM 420	10000	12000	1000	1300	850	850



SELECTION BELT WITH COMMODE GROUP

OUR SELECTION BELTS PROVIDE HEALTHY SELECTION PROCESS WITH DIFFERENT PRODUCTS REGULARY. BECAUSE OF THE APPARATUS LOCATED ON THE EXIT CHUTE, PRODUCTS CAN BE FILLED DIRECTLY INTO THE PACKAGES . THUS, PRODUCTS CAN BE PACKAGED WITHOUT MISUSING AND WITH LOWER PRICE. OUR SELECTION BELTS WHICH ARE SEEN IN THE PICTURES, IN THREE STANDARD TYPE, WITH THREE WAYS, WITH LIGHT AND WITH DEPOT FOR ACUPLE PRODUCTS. ACCORDING TO THE CUSTOMERS' NEEDS, BELT FOR FEEDING THE PRODUCTS CAN BE INSTALLED ON THE MACHINE. BY THE HELP OF SPEED CONTROL DEVICE, SPEED OF WALKING BELT CAN BE HOLDED AT ANY LEVEL. BELT USED ON THE MACHINE IS APPROPRIATE FOR REGULATIONS OF GOOD. BELTS ARE MANUFACTURED IN WHITE, DARK BLUE AND GREEN COLOUR ACCORDING TO THE PRODUCT TYPE. ALL OF THE COMPONENTS OF THE MACHINE ARE MANUFACTURED FROM CrNi (CHROMIUM NICKEL) OF QUALITY 304.

TECHNICAL SPECIFICATIONS

Model	OPM 424	OPM 425	OPM 426	OPM 428	OPM 430
Belt Usage Length	4000 mm	5000 mm	6000 mm	8000 mm	10000 mm
Belt Usage Width	750 mm	750 mm	750 mm	750 mm	750 mm
Depot Capacity	100 Kg.	100 Kg.	100 Kg.	100 Kg.	100 Kg.
Motor Power	0,55 Kw	0,55 Kw	0,75 Kw	1,1 Kw	1,1 Kw
Belt Speed (Max)	6 Mt/Min.	6 Mt/Min.	6 Mt/Min.	7 Mt/Min.	7 Mt/Min.
Quality of Material	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi	304 Quality CrNi

MEASUREMENTS (mm)

	Chassis Length	Total Length	Total Width	Total Height	Chassis Height	Chassis Width
OPM 424	4000	6000	1600	1650	1250	850
OPM 425	5000	7000	1600	1650	1250	850
OPM 426	6000	8000	1600	1650	1250	850
OPM 428	8000	10000	1600	1650	1250	850
OPM 430	10000	12000	1600	1650	1250	850